



SERVGAS PTY. LTD.
Hot Water Co.

AQUA POWERED

**INTERNAL BALANCED FLUE
CONTINUOUS HOT WATER
SYSTEM**



“Under Bench” Hot Water Service

- Supplied with exhaust and inlet ducting.
- Flue is adjustable up to 400mm wall thickness
- Can be installed from INSIDE the house. Suitable for high-rise buildings or where access for installation is limited.
- Compact - will replace most existing under bench type heaters without any alterations to the brickwork.
- Attractively finished - tough heat resistant powder coat polyester paint.
- Supplies up to 600 litres of hot water per hour.



SERVGAS PTY. LTD.
Hot Water Co.

AQUA POWERED

**INTERNAL BALANCED FLUE
CONTINUOUS HOT WATER
SYSTEM**

CONTENTS

General Description

Installation

Pipe Connections

Initial Lighting Procedure

Water Temperature Adjustment

Spare Parts

Data Plate Details

Installing Balanced Flue

Water Pressure

Burner Pressure Adjustment

Maintenance

Sales

For your safety

If you smell gas:

1. Close gas isolating cock
2. Open windows
3. Do not actuate any electrical switches
4. Extinguish naked flames
5. Contact gas authorities immediately.

Do not store or use flammable materials or liquids near the appliance.
Do not place articles on or against this appliance.

Approved for indoor installation only.

WARNING

**SCALDING OCCURS AT 50° C
THIS APPLIANCE IS CAPABLE
OF PROVIDING HOT WATER
AT ABOVE THIS TEMPERATURE**

THE APPLIANCE MAY ONLY BE INSTALLED BY AN AUTHORISED PERSON

- Perfect functioning of the appliance is guaranteed only if this specification and the operating instructions are followed.
- The customer shall be provided with these installation instructions.
- The fitter shall explain the function and operation of the appliance to the customer.
- Servicing may only be carried out by authorised personnel.
- Installation in a marine environment should be avoided.
- Install in accordance with AS5601 and AS 3500.4 and all local building, water and gas firing regulations.
- Not suitable for pool or SPA application.
- Failure to install the appliance in accordance with these installation instructions may void warranty.